

THE PREPARATION OF NATURAL WOOD, BEFORE THE APPLICATION OF A FINISH

WORLD ASSOCIATION OF TECHNOLOGY TEACHERS <https://www.facebook.com/groups/254963448192823/> www.technologystudent.com © 2017 V.Ryan © 2017

V.Ryan © 2000 - 2017

On behalf of The World Association of Technology Teachers

W.A.T.T.



World Association of Technology Teachers

This exercise can be printed and used by teachers and students. It is recommended that you view the website (www.technologystudent.com) before attempting the design sheet .

THESE MATERIALS CAN BE PRINTED AND USED BY TEACHERS AND STUDENTS.
THEY MUST NOT BE EDITED IN ANY WAY OR PLACED ON ANY OTHER MEDIA INCLUDING WEB SITES AND INTRANETS.
NOT FOR COMMERCIAL USE.
THIS WORK IS PROTECTED BY COPYRIGHT LAW.
IT IS ILLEGAL TO DISPLAY THIS WORK ON ANY WEBSITE/MEDIA STORAGE OTHER THAN www.technologystudent.com

THE PREPARATION OF NATURAL WOOD, BEFORE THE APPLICATION OF A FINISH

1. Why is a finish often applied to the surface of natural wood?

4 marks

2. Describe some of the problems associated with the initial preparation of the surface of natural wood.

4 marks

3. With the aid of diagrams, name one natural wood filler and describe how it is used to repair cracks and holes *8 marks*